

CXL4.5-12

12V 4.5AH

Extended Life



CXL4.5-12

Awaiting Image

Physical Specification


Part Number:	CXL4.5-12
Length:	151 ± 3 mm (5.94 inches)
Width:	53 ± 3 mm (2.09 inches)
Container Height:	93 ± 3 mm (3.66 inches)
Total Height (with terminal):	99 ± 3 mm (3.90 inches)
Approx Weight:	Approx 1.9 Kg (4.19 lbs)

Specifications

	Nominal Voltage	12V	
	Nominal Capacity (10HR)	4.5AH	
Terminal Type	Standard Terminal	T1	
	Optional Terminal	T2	
Container Material	Standard Option	ABS	
	Flame Retardant Option (FR)	ABS (UL94:VO)	
Rated Capacity	4.77 AH/0.239A	(20hr,1.80V/cell, 25°C / 77°F)	
	4.50 AH/0.45A	(10hr,1.80V/cell, 25°C / 77°F)	
	3.80 AH/0.76A	(5hr,1.75V/cell, 25°C / 77°F)	
	3.48 AH/1.16A	(3hr,1.75V/cell, 25°C / 77°F)	
	2.77 AH/2.77A	(1hr,1.60V/cell, 25°C / 77°F)	
Max Discharge Current	67.5A (5s)		
Internal Resistance	Approx 35.0mΩ		
Discharge Characteristics	Operating Temp. Range	Discharge: -15 ~ 50°C (5 ~ 122°F)	
		Charge: 0 ~ 40°C (32 ~ 104°F)	
		Storage: -15 ~ 40°C (5 ~ 104°F)	
	Nominal Operating Temp. Range	25 ± 3°C (77 ± 5°F)	
	Cycle Use	Initial Charging Current less than 1.35A.Voltage 14.4V ~ 15.0V at 25°C (77°F) Temp. Coefficient -30mV/°C	
	Standby Use	No limit on Initial Charging Current Voltage 13.5V ~ 13.8V at 25°C (77°F) Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%	
	25°C (77°F)	100%	
	0°C (32°F)	86%	
Design Floating Life at 20°C	15 Years		
Self Discharge	Canbat batteries may be stored for up to 6 months at 25°C(77°F) and then a refresh charge is required. For higher temperatures the time interval will be shorter.		

Dimensions

T1 Terminal



ALL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE


Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	5.80	4.84	4.13	3.37	2.55	2.14	1.36	1.08	0.88	0.71	0.62	0.497	0.425	0.236
1.80V/cell	7.42	5.85	4.88	3.98	2.97	2.40	1.49	1.16	0.94	0.76	0.67	0.528	0.450	0.239
1.75V/cell	8.15	6.39	5.25	4.13	3.08	2.51	1.54	1.18	0.96	0.78	0.68	0.537	0.455	0.241
1.70V/cell	8.88	6.82	5.52	4.30	3.20	2.59	1.61	1.22	0.98	0.80	0.70	0.545	0.459	0.245
1.65V/cell	9.59	7.26	5.86	4.54	3.28	2.67	1.65	1.27	1.02	0.82	0.71	0.553	0.468	0.248
1.60V/cell	10.4	7.76	6.24	4.79	3.42	2.77	1.71	1.31	1.05	0.85	0.73	0.558	0.473	0.250


Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	10.9	9.21	7.93	6.55	4.99	4.20	2.70	2.15	1.74	1.41	1.24	0.999	0.856	0.476
1.80V/cell	13.8	11.0	9.23	7.61	5.76	4.68	2.93	2.30	1.85	1.51	1.33	1.058	0.905	0.480
1.75V/cell	14.9	11.8	9.84	7.83	5.92	4.87	3.02	2.33	1.89	1.55	1.36	1.073	0.913	0.484
1.70V/cell	15.9	12.5	10.3	8.11	6.14	5.01	3.14	2.39	1.93	1.58	1.39	1.087	0.921	0.493
1.65V/cell	17.0	13.2	10.8	8.49	6.23	5.14	3.21	2.48	1.99	1.62	1.41	1.102	0.939	0.499
1.60V/cell	18.1	13.9	11.4	8.90	6.46	5.30	3.30	2.55	2.05	1.67	1.44	1.110	0.947	0.500


Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Self Discharge Characteristics



A

No supplementary required
(Carryout supplementary charge before use if 100% capacity is required.)

B

Supplementary charge required before use. Optional charging way as below:
 1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
 2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.25V/cell.
 3. Charged for 8 ~ 10 hours at limited current 0.05 CA.

C

Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.

ALL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE