

Section 1 product and company identification

Product Name:	Valve Regulated Lead Acid Battery	Phone	1.778.358.3925
Company Name:	Canbat Batteries, a reseller of LEOCH	Email	info@canbat.ca
Company Address:	600-1285 West Broadway, Vancouver BC, V6H 3X8, Canada		

Section 2 composition/information ingredients

Pure chemical Mixture

Chemical Ingredient	Molecular	Content	CAS No.
Lead and lead oxide	Pb, PbO ₂	60-70	7439-92-1,1309-60-0
Calcium	Ca	<0.15	7440-70-2
Tin	Sn	<1	7440-31-5
Sulfuric acid	H ₂ SO ₄	10-15	7664-93-9
ABS		5-10	9003-56-9
AGM Separator		3-4	

Section 3 hazards summarizing

Classification of Danger: (refer to section 14)

Invasion Route: eyes, skin contact, and ingestion.

Health Hazard:

The valve regulated lead-acid batteries are not hazardous when used according to the instructions of the manufacturer under normal conditions. In case of misuse, there may be a risk of rupture, fire, heat, leakage of internal components, with could cause casualty loss. Contact with internal components may cause irritation or burns to eyes and skin. Misuse include but not limited to the following cases: charged for long time, short circuited, put into fire, whacked with hard object, punctured with acute object, crushed, and broken.

Environmental Hazard

The internal electrolyte may cause adverse environmental impacts if

The Danger of Burning and Exploding

May occur fire or explosion in high temperature or short circuit.

Section 4 first-aid measures

The valve regulated lead acid batteries are not hazardous with eye and skin contact under normal circumstance. In case of internal hazardous substance leaking, the following measures should be taken if body parts come in contact with these substance:

AFTER SKIN CONTACT

Immediately wash skin with soap and copious amounts of water.

AFTER EYE CONTACT

Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

AFTER INHALATION:

Inhale fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

AFTER INGESTION:

If swallowed, wash out mouth with water provided person is conscious. Call a physician.

Section 5 fire-fighting measures

- Characteristics of Hazard: Toxic fumes; gases or vapors may evolve on burning.
- Hazardous Combustion Products: CO, CO₂, acid, hydrogen and oxygen gas.
- Fire-extinguishing Methods: Carbon dioxide, dry chemical powder, or appropriate foam.
- Attention in Fire-extinguishing: Wear anti-gas masks and full fire-fighting suits.

Section 6 accidental release measures

If the battery is missed and leakage occurs, liquid could be absorbed with sands, earth, or other inert substance, and the contaminated area should be ventilated in the meantime. Damaged batteries that are not hot or burning should be placed in a sealed plastic bag or container.

Section 7 handling and storage

Handling: Do not handle the batteries in a manner that allows terminals to short circuit

Storage: Store and used far away from heat, sparks, open flame, or other heat ignition sources, and under room temperature (<30°C) in ventilating and dehumidifying environments.

Section 8 exposure controls/personal protection

Maximum Allowable Concentration: No Standard available

Engineering Controls: No engineering controls are required for handling batteries that have not been damaged. Personal protective equipment for damaged batteries should include chemical resistant gloves and safety glasses.

Section 9 Physical and Chemical Properties

Not applicable to our products

Section 10 stability and reactivity

Stability: Stable under normal temperatures and pressures.

Incompatibility: Oxidizing agents

Conditions to Avoiding: Heat and open flame, short circuit, and water

Hazardous polymerization: Will not occur

Decomposition Products: CO, CO₂, acid, hydrogen and oxygen gas

Section 11 toxicological information

VRLA batteries do not elicit toxicological properties during routine handling and use.

Section 12 ecological information

Ecological toxicity: N/A

Biodegradability: N/A

Non-biodegradability: N/A

Section 13 disposal

- **Waste Treatment:** Recycle or dispose of batteries in accordance with local regulations.
- **Attention for Waste Treatment:** Deserted batteries couldn't be treated as ordinary trash. Couldn't be thrown into fire or placed in high temperature. **Batteries must not be dissected, pierced, crushed or treated similarly. Best way is recycling.**

Section 14 transport information

UN NO. N/A

Proper shipping name: N/A

Packing group: N/A

ICAO/IATA	IMDG CODE	DOT
Not- regulated	Not- regulated	Not- regulated
Can be shipped by air in accordance with International Air Transport Association(IATA), DGR Packing Instructions(PI), PI872 appropriate and Special Provision A67	International Maritime Organization(IMO) under Special Provision 238	Non-Spillable Battery complies with provisions listed in 49 CFR 173.159(d), therefore must not be marked with an ID number or hazardous label and is not subject to hazardous shipping paper requirements.

Section 15 regulatory information

Recommendations on the transport of dangerous goods-model regulations (15th revised), IATA dangerous goods regulations, International Maritime Dangerous Goods Code, U.S. Hazardous Material Regulations

Section 16 other information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.

This information has been provided to Canbat Batteries by the manufacturer:

ANHUI LEOCH POWER SUPPLY CORP.

Economic development zone, Suixi town,
Huaibei city, Anhui Province, China.

Tel: 0086-755-26067200(100 lines)

Fax: 0086-755-26067269,26067217